



MODEL NO. _____ A930TA-70
 CAPACITY _____ 70,000 GR.
 * NORMAL FLOW _____ 14 GPM @ 15 PSI DROP
 * PEAK FLOW _____ 19 GPM @ 25 PSI DROP
 BW RATE _____ 1.7 GPM
 MINERAL TANK _____ 12" DIA X 52" HEIGHT
 MEDIA VOL. _____ 2.33 CU/FT
 BRINE TANK _____ 18" DIA X 40" HEIGHT
 SALT CAPACITY _____ 320 LBS

ACCESSORIES:

WATER METER _____ INTERNAL TURBINE

WEIGHT:

SHIPPING _____ 300 LBS
 OPERATING _____ 1,030 LBS

PIPE SIZE:

INLET _____ 1" Sweat
 OUTLET _____ 1" Sweat
 DRAIN _____ 1/2" Tube
 BRINE _____ 3/8" Tube

NOTES:

DASHED PIPING, FITTINGS AND VALVES SUPPLIED BY OTHERS.

ALSO AVAILABLE IN 3/4" PIPE CONNECTIONS

DO NOT SOLDER PIPES WHILE CONNECTORS ARE ATTACHED TO THE CONTROL VALVE

* QUALITY OF WATER MAY VARY DEPENDING UPON FLOW RATE AND WATER CONDITIONS

DIMENSIONS:

A: _____ 62"
 B: _____ 12"
 C: _____ 18"
 D: _____ 40"

All Dimensions are +/- 2"



PACIFICWATER
INC.

THIS DRAWING AND ALL OF THE DESIGN INFORMATION ARE THE SOLE PROPERTY OF THE SYSTEM MANUFACTURER. THIS DRAWING IS NOT TO BE DISCLOSED OR COPIED WITHOUT THE WRITTEN AUTHORIZATION FROM THE SYSTEM MANUFACTURER.

TWIN ALTERNATING SYSTEM 7			
GENERAL ARRANGEMENT			
DRAWN BY		DATE	DWG. NO.
SCALE		10/01/19	A930TA.tif
CHECKED BY			
APPROVED BY			